

SERIES 320 eSafe

PRICE GROUP A

eSafe



eSafe Series 320 coupling is an easy-to-handle high performing coupling with a long service life. eSafe is a one hand operated safety coupling that vents before disconnection eliminating the risk of hose whip. Male threads on the couplings and nipples feature pre-applied thread sealant. The couplings have a smaller outside dimension than comparable designs. Full automatic operation ensures easy handling. eSafe complies with ISO Standard 4414 and EN 983.

Technical Data

Nominal flow diameter	7,6 mm
Airflow	2250/min
Max. working pressure	16 bar
Min. burst pressure	140 bar
Temperature range	- 20 °C - + 1000 °C
Material	Hardened zinc-plated steel
Connection force	86,0 N
Interchangeable with	Tema 1600, Rectus 25

COUPLING, e-Safe	Size	Part No.	€/pc VAT 0 %	
Hose connection		6,3 mm (1/4")	10 320 2002	29,75
		8 mm (5/16")	10 320 2003	29,75
		10 mm (3/8")	10 320 2004	29,75
		13 mm (1/2")	10 320 2005	30,60
		9 mm	10 320 2009	30,60
Male thread		R 1/4"	10 320 2152	29,75
		R 3/8"	10 320 2154	29,75
		R 1/2"	10 320 2155	30,60
Female thread		G 1/4"	10 320 2202	29,75
		G 3/8"	10 320 2204	29,75
		G 1/2"	10 320 2205	30,60
Stream-Line connection		5 x 8 mm	10 320 2058	34,15
		6,5 x 10 mm	10 320 2060	34,15
		8 x 12 mm	10 320 2062	34,20
		9,5 x 13,5 mm	10 320 2063	34,90
		11 x 16 mm	10 320 2066	37,00
		13 x 18 mm	10 320 2068	44,15
eSafe Soft-Line				
Stream-Line connection		6,5 x 10 mm	10 320 2080	50,00
		11 x 16 mm	10 320 2085	52,85
eSafe with Locking ring				
Stream-Line connection		6,5 x 10 mm	10 320 2090	47,75
		8 x 12 mm	10 320 2092	47,75
		11 x 16 mm	10 320 2096	55,45
Female thread		G 3/8"	10 320 2244	42,60



320 Soft-Line

[Click here for table of contents](#)